

TYPE  
**HPI**

**Features**

- Five year tool warranty
- 18 V, 5.0 Ah Milwaukee Li-ion battery, 3 year warranty
- Auto cut detection
- USB interface
- Light weight/Compact design
- LED operating indicator lights
- LED battery charge indicator
- Manual release switch
- Quick disconnect couplers
- Return adjustment knob
- Closed oil system

**Benefits**

- Ensures confidence for durability & quality
- Eliminates need for external power source
- Extends motor life
- Capture data for performance, reporting & service
- Reduces fatigue & saves space
- Identifies condition and readiness of pump
- Job site battery management
- Emergency safety release, even without battery
- Leak free connection
- Faster crimp cycles
- Allows pump to function, even upside down



Catalog Number	Description
TB-PMP	Pump Kit
TB-PMPX	Pump Kit w/o batteries and charger
<b>Specifications</b>	
Force Developed	10,000 psi
Compression Head Max	60 ton
Hose Length	5 ft.
Weight with 5.0 Battery	11.4 lbs
Oil Capacity	25 oz.
<b>Battery Life Estimates</b>	
18V DC - 5.0 Ah	250

**Kit Includes:**

- Pump
- 2 Milwaukee Batteries - 18V 5.0 Ah
- 1 Milwaukee Battery Charger - 120V AC
- 5 ft. Non-conductive Filled Hose
- 5 ft. Hand Held Remote Pump Cord
- Shoulder Strap for Pump
- USB 2.0 Cable Type A to Mini-B, 6 ft.
- Durable Carrying Bag
- Instruction Manual
- Male/Female Adapters

## TYPE HPI

### Features

- Five year tool warranty
- 18 V, 5.0 Ah Milwaukee Li-ion battery, 3 year warranty
- Auto cut detection
- USB interface
- Light weight/Compact design
- LED operating indicator lights
- LED battery charge indicator
- Manual release switch
- Quick disconnect couplers
- Return adjustment knob
- Closed oil system

### Benefits

- Ensures confidence for durability & quality
- Eliminates need for external power source
- Extends motor life
- Capture data for performance, reporting & service
- Reduces fatigue & saves space
- Identifies condition and readiness of pump
- Job site battery management
- Emergency safety release, even without battery
- Leak free connection
- Faster crimp cycles
- Allows pump to function, even upside down




Fig. 1



Fig. 2



Fig. 3



Fig. 4



Fig. 5



Fig. 6



Fig. 7



Fig. 8

Figure Number	Catalog Number	Description
Fig. 1	HSO-5	5 ft. Non-conductive filled hose
Fig. 1	HSO-10	10 ft. Non-conductive filled hose
Fig. 1	HSO-15	15 ft. Non-conductive filled hose
Fig. 1	HSO-30	30 ft. Non-conductive filled hose
Fig. 2	HSA-5	5 ft. Armored filled hose
Fig. 2	HSA-10	10 ft. Armored filled hose
Fig. 2	HSA-15	15 ft. Armored filled hose
Fig. 2	HSA-30	30 ft. Armored filled hose
Fig. 3	CH-120V	120V Battery charger
Fig. 4	CH-12V	12V Battery charger
Fig. 5	BAT-1850	18V 5.0 Ah Milwaukee Li-ion battery
Fig. 6	RCPMP-5	5 ft. Hand held remote pump cord
-	SHST	Shoulder strap for pump
-	USB	6 ft. 2.0 Cable Type A to Mini-B
Fig. 7	QCA-M	Male adapter
Fig. 8	QCA-F	Female adapter